NICKEL ALLOY

718 - 2,4668



718 - 2.4668

Nickel Alloy 718, with the designation UNS N07718 and the DIN/EN designation 2.4668, is a precipitation-hardening nickel-chromium alloy. It has excellent resistance to corrosion and oxidation, as well as high tensile and fatigue strength at high temperatures, and is widely used in aerospace, oil and gas, and other high-performance applications.

KEY FEATURES

- High strength
- Good corrosion resistance
- High temperature stability
- Good weldability

CHE	MIC	AL PR	OPER	TIE	S								
Nickel	Chromium	Niobium	Molybdenum		Titanium	Manganese		Copper		Phosphorus	Carbon	Sulphur	Iron
(Ni)	(Cr)	(Nb)	(Mo)	(Co)	(Ti)	(Mn)	(Si)	(Cu)	(AI)	(P)	(C)	(S)	(Fe)
50-55%	17-21%	4.75-5.5%	2.8-3.3%	1%	0.65-1.15%	0.35%	0.35%	0.3%	0.2-0.8%	0.15%	0.08%	0.02%	rest

MECHANICAL PROPERTIES				
Tensile strength (N/mm²)	725			
Yield strength (N/mm²)	325			
Elongation (% in 4D)	30			
Hardness - Rockwell C (HRC) max	40-45			
Hardness - Brinell (HB) max	331			

PHYSICAL PROPERTIES						
Density (kg/m³)	8220					
Modulus of elasticity (Gp	200					
Manage of Circles of	0-100°C (µm/m/°C)	12.8				
Mean coefficient of	0-350°C (µm/m/°C)	13.4				
thermal expansion	0-538°C (µm/m/°C)	14.1				
Thermal	at 100°C (W/m.K)	11.4				
conductivity	at 500°C (W/m.K)	14.3				
Specific Heat 0-100°C (J	435					
Electrical resistivity (nΩ.	132					
Melting point (°C)	1335					

MARKET SECTORS



Turbocharger rotors, fasteners, components





Downhole equipment, wellhead components, oil well tools



cryogenic tanks

Surgical instruments, medical implants, components



Reactors, nuclear fuel elements



Aerospace Industry

Turbine disks, engine parts, structural elements



Tel: +44 (0)1204 368600 Visit our website:
Email: sales@steel-dynamics.co.uk www.steel-dynamics.co.uk